



TOLERANCES: ±0.05

- NOTES:
- INSULATOR: LCP, COLOR-BLACK
  - USB CONTACT: PHOSPHOR BRONZE, 0.15mm THICKNESS, GOLD PLATED ON CONTACT AREA, GOLD FLASH OR 50 U" TIN PLATED ON SOLDER TAIL, 80 U" MIN. NICKEL UNDER PLATED OVERALL
  - SHELL: STAINLESS STEEL, 0.3 THICKNESS, 30U" NICKEL PLATED ON THE SOLDERING TAB.

Pin Assignments			
Shell	Shield		
10	MicB_SSRX+		
9	MicB_SSRX-		
8	GND_DRAIN		
7	MicB_SSTX+		
6	MicB_SSTX-		
5	GND		
4	ID		

MUB3B-05XXX3X1

Foot Long:  
 1: 1.60mm  
 2: 1.20mm  
 6: 1.00mm

Color:  
 B: Black R: Red  
 E: Blue G: Green  
 Y: Yellow W: White

Contact Finish?  
 00: Material 10: 10u"Gold  
 01: G/F 15: 15u"Gold  
 05?5u"Gold 30: 30u"Gold

ITEM	DESCRIPTION	PIN NO.	SIGNAL NAME
3	CONTACT	3	D+
2	SHELL	2	D-
1	HOUSING	1	VBUS

TOLERANCE:	UNIT		深圳市同心富精密电子有限公司 Shenzhen TXF Precision Electronics Co.,LTD	
X. ± 0.50 X.* ± 1°	MM		DRAW:	2010.12.13
.X ± 0.30 .X.* ± 1°	SHEET	DESIGN:		
.XX ± 0.20 .XX.* ± 1.0°	1/1	CHECK:		
.XXX ± 0.10	SCALE	APPR:		
	1:1	REV:D		

SP/N: MUB3B-07XXX3X1  
 ITEM: Micro USB 3.0 B/F SMT ( 壳DIP SHELL)  
 DRW NO: C-MUB3B-07XXX3X1

LTR	ECN NO	REVISION	RECORD	DRAW	DATE
1					